

M-Euro 5w30

FULLY SYNTHETIC, LOW SAPS, ACEA C3, A5, B3 PASSENGER VEHICLE DIESEL LUBRICANT

DESCRIPTION

M-Euro 5w30 is a high performance technically advanced fully synthetic low saps lubricant. Specially formulated for late model passenger motor vehicles including those fitted with diesel particulate filters (DPF's).

M-Euro 5w30 meets and complies with the demanding requirements of Euro 4 exhaust emission legislation. Formulated to meet API SM requirements, M-Euro 5w30 is ideally designed for European vehicles calling for the ACEA C3 specification such as VW, BMW and other European vehicles. M-Euro 5w30 also meets BMW long-life LL-04, Mercedes-Benz 229.51 specifications.

FEATURES & BENEFITS

- Technically advanced Synthetic formulation
- Suitable for use where diesel particulate filters (DPF's) are required
- Extended drain intervals
- Advanced soot and sludge control
- Reduces fuel consumption
- Environmentally friendly, ensures that the engine's anti-pollution systems for optimum perform

MEETS THE FOLLOWING SPECIFICATIONS:

- ACEA A5 (2007)
- ACEA B3/B4/B5 (2007)
- ACEA C2/C3-08 / Euro 4 Exhaust emission Legislation
- ACEA C2/C3 10
- GM Dexos 2
- API SN/CF
- MB 229.51

- BMW Longlife-04
- Volkswagen VW50200
- Volkswagen VW50500
- Volkswagen VW50501
- Porsche
- PSA Peugeot Citroen B7 12290
- Ford WSS-M2C-913C



M-Euro 5w30

FULLY SYNTHETIC, LOW SAPS, ACEA C3, A5, B3 PASSENGER VEHICLE DIESEL LUBRICANT

TYPICAL CHARACTERISTICS

	TEST METHOD	UNITS	RESULTS
Density @ 15°C	ASTM D1298	kg/L	0.88
Kinematic Viscosity		5/2	
@ 40°C	ASTM D445	cSt	60
@ 100°C	ASTM D445	cSt	10.0
Viscosity Index	ASTM D2270		>150
Pour Point	ASTM D97	°C	-34
Flash Point (COC)	ASTM D92	°C	210
Total Base Number	ASTM D2896	mgKOH/g	7.9
Sulphated Ash	ASTM D874	% mass	<1.00

THE FEATURES MENTIONED ABOVE ARE AVERAGE VALUES OBTAINED WITH SOME VARIABILITY IN PRODUCTION AND DO NOT CONSTITUTE A SPECIFICATION

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained from our website www.monsterlubricants.com.au.

PO BOX 442

RAMSGATE NSW 2217
INFO@MONSTERLUBRICANTS.COM.AU
WWW.MONSTERLUBRICANTS.COM.AU