

# M-Euro C1 5w30

SYNTHETIC, ULTRA LOW SAPS, ACEA C1 PASSENGER CAR DIESEL OIL

### DESCRIPTION

M-Euro C1 5w30 is a fully synthetic high performance, ultra-low SAPS passenger car engine oil for use in diesel and some petrol fuelled cars that specifically call for an ACEA C1 or DL-1 rated oil such as some Mazda, Ford, Mitsubishi and Citroen diesels fitted with Diesel Particulate Filters (DPF's).

M-Euro C1 5w30 is a high quality formulation will maximise DPF life, maximises fuel economy and helps extend drain intervals. Note: M-Euro C1 should only be used where it is specifically recommended by Monster Lubricants or where an ACEA C1 specifications is called for. M-Euro C1 5w30 is a highly specialised formulation that may not be suitable for many modern passenger cars that do not call for an ACEA C1 rated oil. Not suitable for use where an ACEA C2, C3 or C4 specification is recommended.

### **FEATURES & BENEFITS**

- Ultra-Low sulphated ash content (<0.50%/wt)
- Fully Synthetic European formulation
- Low Zinc (<0.055%/Wt) and low Phosphorus (<0.050%/Wt) formulation
- Environmentally friendly formulation.
- Maximises fuel economy.
- Excellent thermal stability and low temperature performance.
- Offers excellent catalyst protection (Diesel Particulate Filter).
- Specifically designed for vehicles calling for an ACEA C1 or DL-1 specification.

## MEETS THE FOLLOWING SPECIFICATIONS:

- ACEA C1 2007
- DL-1
- SAE 5w30



# M-Euro C1 5w30

SYNTHETIC, ULTRA LOW SAPS, ACEA C1 PASSENGER CAR DIESEL OIL

### TYPICAL CHARACTERISTICS

	TEST METHOD	UNITS	RESULTS
Density @ 15°C	ASTM D1298	kg/L	0.88
Kinematic Viscosity		EJ-	
@ 40°C	ASTM D445	cSt	60
@ 100°C	ASTM D445	cSt	10
Viscosity Index	ASTM D2270		>165
Pour Point	ASTM D97	°C	-34
Total Base Number	FTIR	mgKOH/g	6.02
Sulphated Ash	2 A		<0.50

THE FEATURES MENTIONED ABOVE ARE AVERAGE VALUES OBTAINED WITH SOME VARIABILITY IN PRODUCTION AND DO NOT CONSTITUTE A SPECIFICATION

#### **STORAGE**

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

#### HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained from our website www.monsterlubricants.com.au.

> PO BOX 442 RAMSGATE NSW 2217 INFO@MONSTERLUBRICANTS.COM.AU WWW.MONSTERLUBRICANTS.COM.AU