



M-Euro C4 5w30

FULLY SYNTHETIC, ULTRA LOW SAPS, ACEA C4 PASSENGER CAR DIESEL OIL

DESCRIPTION

M-Euro C4 5w30 is a fully synthetic high performance, ultra-low SAPS passenger car engine oil for use in diesel and some petrol fuelled cars that specifically call for an ACEA C4, Ford M2C934-B or Renault RN 0720 specifications. Applications include selected Nissan (Navara / Pathfinder), Samsung, Land Rover, Suzuki, Renault and Jaguar where ACEA C4 is called for. May be used where ACEA C4 is called for.

M-Euro C4 5w30 is a high quality formulation will maximise DPF life, maximises fuel economy and helps extend drain intervals. Note: M-Euro C4 should only be used where it is specifically recommended by Monster Lubricants or where an ACEA C4 specifications is called for. M-Euro C4 5w30 is a highly specialised formulation that may not be suitable for many modern passenger cars that do not call for an ACEA C4 rated oil. Not suitable for use where an ACEA C2 or C3 specification is recommended.

FEATURES & BENEFITS

- Ultra-Low sulphated ash content (<0.50%/wt)
- Fully Synthetic European formulation
- Low Zinc (<0.055%/Wt) and low Phosphorus (<0.050%/Wt) formulation
- Environmentally friendly formulation
- Maximises fueleconomy
- Excellent thermal stability and low temperature performance
- Offers excellent catalyst protection (Diesel Particulate Filter)
- Specifically designed for vehicles calling for an ACEA C4 specification

MEETS THE FOLLOWING SPECIFICATIONS:

- ACEA C4 – 2012
- Renault RN 0720
- MB 229.51-226.51
- Ford M2C934-B
- SAE 5w30



M-Euro C4 5w30

FULLY SYNTHETIC, ULTRA LOW SAPS, ACEA C4 PASSENGER CAR DIESEL OIL

TYPICAL CHARACTERISTICS

	TEST METHOD	UNITS	RESULTS
Density @ 15°C	ASTM D1298	kg/L	0.88
Kinematic Viscosity			
@ 40°C	ASTM D445	cSt	63
@ 100°C	ASTM D445	cSt	10.6
Viscosity Index	ASTM D2270		>159
Pour Point	ASTM D97	°C	-34
Total Base Number	FTIR	mgKOH/g	6.02
Sulphated Ash			<0.50

THE FEATURES MENTIONED ABOVE ARE AVERAGE VALUES OBTAINED WITH SOME VARIABILITY IN PRODUCTION AND DO NOT CONSTITUTE A SPECIFICATION

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained from our website www.monsterlubricants.com.au.

PO BOX 442
RAMSGATE NSW 2217
INFO@MONSTERLUBRICANTS.COM.AU
WWW.MONSTERLUBRICANTS.COM.AU