



M-Pro 10w30

API SN/SM/SL/SJ/CF ILSAC GF-5

DESCRIPTION

M-Pro SAE 10w30 is a technically advanced engine lubricant designed to provide excellent fuel efficiency and minimal engine wear, particularly at cold start ups, formulated using the latest in API additive technology. Exceeding the needs of today's more demanding modern engines using the latest additives designed to extend the life of your engine and reduce sludge.

M-Pro SAE 10w30 is suitable for Petrol, Diesel, LPG cars, light commercial vehicles and 4WDs where API SN/SM/SL/SJ/CF ILSAC GF-5 or earlier specifications are recommended.

FEATURES & BENEFITS

- Rapid oil flow at start up, minimising engine wear
- Actively locks away harmful performance robbing deposits
- Helps to remove sludge left behind by inferior oils
- Helps to protect against wear and neutralizes corrosive combustion acids
- Helps to maintain protection throughout the oil-drain interval

MEETS THE FOLLOWING SPECIFICATIONS:

- SAE Viscosity 10w30
- API SN/ILSAC GF-5
- FORD WSS-M2C-945A/946A
- CHRYSLER MS 6395
- GM 6094M

M-Pro 10w30

API SN/SM/SL/SJ/CF ILSAC GF-5

TYPICAL CHARACTERISTICS

	TEST METHOD	UNITS	RESULTS
Density @ 15°C	ASTM D1298	kg/L	0.86
Kinematic Viscosity			
@ 40°C	ASTM D445	cSt	68
@ 100°C	ASTM D445	cSt	10.6
Viscosity Index	ASTM D2270		150min.
Pour Point	ASTM D97	°C	-30
Flash Point (COC)	ASTM D92	°C	>200
Total Base Number	ASTM D2896	mgKOH/g	7.2
Sulphated Ash	ASTM D874	% mass	0.7

THE FEATURES MENTIONED ABOVE ARE AVERAGE VALUES OBTAINED WITH SOME VARIABILITY IN PRODUCTION AND DO NOT CONSTITUTE A SPECIFICATION

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained from our website www.monsterlubricants.com.au.