



# M-Pro 15w40

API SN/SM/SL/SJ/CF

## DESCRIPTION

M-Pro SAE 15w40 is a technically advanced engine lubricant designed to suit modern and older engines making it an excellent mixed fleet lubricant. This technically advanced lubricant minimises engine wear, particularly at cold start ups and is formulated using the latest in API additive technology. This High performance engine lubricant exceeds the needs of todays more demanding modern engines, using technically advanced additives designed to extend the life of your engine and reduce sludge.

M-Pro SAE 15w40 is suitable for vehicles running Petrol, Diesel, LPG or CNG, light commercial vehicles and 4WDs where API SN/SM/SL/SJ/CF or earlier specifications are recommended.

## FEATURES & BENEFITS

- Rapid oil flow at start up, minimising engine wear
- Actively locks away harmful performance-robbing deposits
- Helps to remove sludge
- Helps to protect against wear and neutralize corrosive combustion acids
- Helps to maintain protection throughout the oil-drain interval

## MEETS THE FOLLOWING SPECIFICATIONS:

- SAE Viscosity 15w40
- API SN/CF
- ACEA A2-96, B2-96
- Ford ESE- M2C -153E
- Passes the performance requirements of Japanese VTW
- MIL-L-46152E, 2104E

# M-Pro 15w40

API SN/SM/SL/SJ/CF

## TYPICAL CHARACTERISTICS

	TEST METHOD	UNITS	RESULTS
Density @ 15°C	ASTM D1298	kg/L	0.8847
Kinematic Viscosity			
@ 40°C	ASTM D445	cSt	116
@ 100°C	ASTM D445	cSt	14.9
Viscosity Index	ASTM D2270		129
Pour Point	ASTM D97	°C	-27
Flash Point (COC)	ASTM D92	°C	200
Total Base Number	ASTM D2896	mgKOH/g	6.5
Sulphated Ash	ASTM D874	% mass	1.2

*THE FEATURES MENTIONED ABOVE ARE AVERAGE VALUES OBTAINED WITH SOME VARIABILITY IN PRODUCTION AND DO NOT CONSTITUTE A SPECIFICATION*

## STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

## HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained from our website [www.monsterlubricants.com.au](http://www.monsterlubricants.com.au).

PO BOX 442  
RAMSGATE NSW 2217

[INFO@MONSTERLUBRICANTS.COM.AU](mailto:INFO@MONSTERLUBRICANTS.COM.AU)  
[WWW.MONSTERLUBRICANTS.COM.AU](http://WWW.MONSTERLUBRICANTS.COM.AU)