



# M-Semi 10w40

API SN/SM/SL/SJ/CF ACEA A3/B3

## DESCRIPTION

High performance semi-synthetic engine lubricant is designed to increase protection and drain intervals over mineral oils and exceed the needs of today's more demanding modern engines, using technically advanced additives designed to extend the life of your engine and reduce sludge.

M-Semi SAE 10w40 is a technically advanced engine lubricant designed to provide excellent fuel efficiency and minimal engine wear, particularly at cold start ups and is formulated using the latest in API & ACEA additive technology. M-Semi SAE 10w40 is Suitable Petrol, Diesel, LPG cars, light commercial vehicles and 4WDs where API SN/SM/SL/SJ/CF ACEA A3/B3 or earlier specifications are recommended.

## FEATURES & BENEFITS

- Designed to increase protection and drain intervals over mineral oils
- Provides fuel saving capability
- Provides reduced oxidation and viscosity breakdown
- Rapid flow technology at start up, minimising engine wear
- Actively locks away harmful performance-robbing deposits
- Helps to remove sludge
- Helps to protect against wear and neutralize corrosive combustion acids
- Helps to maintain protection throughout the oil-drain interval

## MEETS THE FOLLOWING SPECIFICATIONS:

- SAE Viscosity 10w40
- API SN/SM/SL/SJ/CF ACEA A3/B3/B4
- FORD WSS-M2C-945A/946A
- CHRYSLER MS 6395
- GM 6094M

# M-Semi 10w40

API SN/SM/SL/SJ/CF ACEA A3/B3

## TYPICAL CHARACTERISTICS

	TEST METHOD	UNITS	RESULTS
Density @ 15°C	ASTM D1298	kg/L	0.887
Kinematic Viscosity			
@ 40°C	ASTM D445	cSt	105
@ 100°C	ASTM D445	cSt	15.0
Viscosity Index	ASTM D2270		136
Pour Point	ASTM D97	°C	-34
Flash Point (COC)	ASTM D92	°C	>224
Total Base Number	ASTM D2896	mgKOH/g	9.02

*THE FEATURES MENTIONED ABOVE ARE AVERAGE VALUES OBTAINED WITH SOME VARIABILITY IN PRODUCTION AND DO NOT CONSTITUTE A SPECIFICATION*

## STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

## HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained from our website [www.monsterlubricants.com.au](http://www.monsterlubricants.com.au).

PO BOX 442  
RAMSGATE NSW 2217

INFO@MONSTERLUBRICANTS.COM.AU  
WWW.MONSTERLUBRICANTS.COM.AU