



M-Agri 10w30

UNIVERSAL TRACTOR TRANSMISSION OIL

DESCRIPTION

M-Agri 10w30 is a technically advanced synthetic fortified Universal Tractor Transmission Oil "UTTO" suited to tractors requiring a common oil for transmissions, power take offs, hydraulics, differentials, final drives, wet clutches and brakes.

M-Agri 10w30 is the latest multipurpose transmission/hydraulic oil designed to work in big horsepower tractors working in the harshest conditions. Meeting a wide range of specifications from most modern tractor and hydraulic pumps.

FEATURES & BENEFITS

- Excellent friction performance ensuring smooth, positive changes with enhanced friction material durability
- Power steering pump wear protection for longer pump life
- Rust and corrosion protection for highly polished and finished surfaces
- Copper corrosion protection for extended thrust and plain bearing life
- Seal compatibility to help oil seals to remain serviceable and minimize oil leaks
- Advanced anti-wear properties to protect hydraulic systems
- Correct frictional characteristics ensure quiet wet brake operation

MEETS THE FOLLOWING SPECIFICATIONS:

HYDRAULIC PUMP PERFORMANCE

- Sperry Vickers/ Eaton I-286-S (industrial)
- M -2950-S (mobile) & I-280-S
- Denison HF-0, HF-1, HF-2
- Sauer Sundstrand/Danfoss Hydraulics Hydro Static Trans Fluid
- Cincinnati Milacron P-68, P-69, P-70 ZF:TEML03, TEMPL06\

JOHN DEERE

- JDM J20c, J14A, J20D (factory Fill) J14 (A, B, C JDT303), J20 (A, B, HYGUARD) J21A, J27

NEW HOLLAND FORD (NEW HOLLAND GROUP)

- ESN-M2C134-D
- (FNHA-2-C-201.00)
- M2C (A TO C)
- M2C86 (A TO C)
- M2C77-A, M2C53-A, M2C48-B & C, M2C41-B FNHA-2-C-200.00*
- (Super All Season Driveline and hydraulic fluid - F200-a") (*Winter grade)
- M2C134-D/FNHA 201.00
- NB 410B MAT 3525



M-Agri 10w30

UNIVERSAL TRACTOR TRANSMISSION OIL

MASSEY FERGUSON

- M -1135 (Trans / hydraulic - Europe) M -1143 (Trans / hydraulic - Europe) M -1145, M -1127, M -1110 M -1129A

CASE CORP (JI CASE AND INTERNATIONAL HARVESTER)

- JIC-145
- MS - 1210
- MS - 1204
- MS - 1205
- MS - 1206 (POWERGUARD PFT)
- MS - 1207 (HY-TRANS PLUS)
- MS - 1209
- B6
- White Farm Q1826, Q-1705, Q-1766, Q-1802 AGCO, Powerfluid 821XL
- Steiger : HYDR TRANS FLUID
- Versatile
- Deutz-Allis 25743 (PF-821 XL), 25741, 246634
- Fiat-Hesston AF-87
- NB 410B
- MAT 3525
- Kubota - UDT Hydraulic Fluid (UTF)

WHITE FARM (OLIVER)

- 1802, 1826, Q-1705, 1722, 1766, 1766B (UTHF TYPE 55, 5J, Q1802)
- AGCO / Duetsx-Allis / Allis- Chalmers Power Fluid 821 XL
- Landini Tractor II Hyd
- Allison C4
- Caterpillar TO-2
- Sperry Vickers M-2950-S, I-286-S Ind
- Clarke TA-12, TA-18, HR500, HR600
- API GL-4

M-Agri 10w30

UNIVERSAL TRACTOR TRANSMISSION OIL

TYPICAL CHARACTERISTICS

	TEST METHOD	UNITS	RESULTS
Density @ 15°C	ASTM D1298	kg/L	0.89
Kinematic Viscosity			
@ 40°C	ASTM D445	cSt	65
@ 100°C	ASTM D445	cSt	9.5 (min)
Viscosity Index	ASTM D2270		125
Pour Point	ASTM D97	°C	-28
Flash Point (COC)	ASTM D92	°C	210

THE FEATURES MENTIONED ABOVE ARE AVERAGE VALUES OBTAINED WITH SOME VARIABILITY IN PRODUCTION AND DO NOT CONSTITUTE A SPECIFICATION

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained from our website www.monsterlubricants.com.au.