



M-Chain & Bar

PROTECTS CHAINS AND BARS OF HIGH PERFORMANCE CHAIN SAWS

DESCRIPTION

M-Chain & Bar protects bars and chains of high performance chain saws. Contains anti-wear additives and tackifiers to protect the bar and chain and minimise "throw-off" from the chain.

FEATURES & BENEFITS

- Excellent adhesion to the chain and bar
- High level of protection ensures longer bar and chain life
- Provides good antirust and storage protection
- Good penetration of chain links

MEETS THE FOLLOWING SPECIFICATIONS:

- Minimum ISO Viscosity 150
- Maximum ISO Viscosity 220

M-Chain & Bar

PROTECTS CHAINS AND BARS OF HIGH PERFORMANCE CHAIN SAWS

TYPICAL CHARACTERISTICS

	TEST METHOD	UNITS	RESULTS
Density @ 15°C	ASTM D1298	kg/L	0.8830
Kinematic Viscosity			
@ 40°C	ASTM D445	cSt	150-220
@ 100°C	ASTM D445	cSt	15.1
Viscosity Index	ASTM D2270		>150
Pour Point	ASTM D97	°C	-12
Flash Point (COC)	ASTM D92	°C	>220

THE FEATURES MENTIONED ABOVE ARE AVERAGE VALUES OBTAINED WITH SOME VARIABILITY IN PRODUCTION AND DO NOT CONSTITUTE A SPECIFICATION

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained from our website www.monsterlubricants.com.au.