

M-Dot 3



M-Stop Dot 3 Clear Brake Fluid is a blend of polyglycol/glycol ethers with corrosion inhibitors and antioxidant.

USE

M-Stop Dot 3 Clear Brake Fluid is a non-petroleum polyglycol based brake fluid designed for vehicles where DOT 3 / SAE J1703 grade brake fluid is specified. The performance of M-Stop Dot 3 Clear Brake Fluid exceeds the minimum requirements of FMVSS 116 (DOT 3), SAE J1703, ISO4925 (class 3) and the Australian Standard, AS1960.1 (class 1) and can be used where these standards are cited.

Brake systems are not perfectly sealed and water absorption during service is inevitable which subsequently lowers the ERBP of the brake fluid. Therefore, in the absence of specific instructions by the vehicle manufacturer, it is recommended that the fluid is replaced every 12 months.

TYPICAL PROPERTIES

ERBP, °C	269
Wet ERBP, °C	150
pH	9.7

SPECIFICATION

Appearance:	Transparent straw to light amber liquid, free from foreign matter
Equilibrium reflux boiling point (ERBP), °C	230 min
Wet ERBP, °C	140 min
Kinematic viscosity, cS @ -40°C	1500 max
Kinematic viscosity, cS @ +100°C	1.5 min
Density, g/cm ³ @ 20°C	1.061 – 1.071
Water, %w/w	0.3 max

Monster brake fluid is tested to the Australian Standard for Brake Fluid: AS1960.1

Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained from our website www.monsterlubricants.com.au

PO BOX 442
Ramsgate NSW 2217
info@monsterlubricants.com.au
www.monsterlubricants.com.au