

M-Dot 4



M-Stop Dot 4 Clear Brake Fluid is a blend of borate esters, alkyl glycol ethers and polyglycols with corrosion inhibitors and an antioxidant.

USE

M-Stop Dot 4 Clear Brake Fluid is suitable for all Australian, European, Asian, Japanese & American engineered vehicles which specify DOT3 or DOT 4 grade brake fluid.

The performance of M-Stop Dot 4 Clear Brake Fluid exceeds the minimum requirements of FMVSS 116 (DOT 4 and DOT 3), SAE J1704, SAE J1703, ISO4925 (class 4) and the Australian Standard, AS1960.1 (class 2) and can be used where these standards are cited.

Brake systems are not perfectly sealed and water absorption during service is inevitable which subsequently lowers the ERBP of the brake fluid. Therefore, in the absence of specific instructions by the vehicle manufacturer, it is recommended that the fluid is replaced every 24 months.

TYPICAL PROPERTIES

ERBP, °C	277
Wet ERBP, °C	161
pH	8.5

SPECIFICATION

Appearance:	Transparent straw to light amber liquid, free from foreign matter
Equilibrium reflux boiling point (ERBP), °C	260 min
Wet ERBP, °C	155 min
Kinematic viscosity, cS @ -40°C	1800 max
Kinematic viscosity, cS @ +100°C	1.5 min
Density, g/cm ³ @ 20°C	1.061 – 1.081
Water, %w/w	0.2

Monster brake fluid is tested to the Australian Standard for Brake Fluid: AS1960.1

Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained from our website www.monsterlubricants.com.au

PO BOX 442
Ramsgate NSW 2217
info@monsterlubricants.com.au
www.monsterlubricants.com.au