



M-Syn 0w20

FULLY SYNTHETIC API SN / ILSAC GF-5, PASSENGER VEHICLE LUBRICANT

DESCRIPTION

M-Syn 0w20 is a 100% technically advanced fully synthetic, fuel-efficient lubricant that delivers the viscosity required by late model, low emission passenger motor vehicles including hybrids. Exceeding industry standards, this oil has been designed to provide superior fuel efficiency and exceptional engine wear, particularly at cold start-ups and is formulated using the latest in API additive technology.

Exceeding the needs of today's more demanding modern engines using the latest additives designed to extend the life of your engine and reduce sludge. M-Syn 0w20 can be used where fuel economy oils are specified such as Toyota 86, Subaru BRZ, Jeep Cherokee and Honda vehicles calling for a 0W-20 engine lubricant.

FEATURES & BENEFITS

- Technically advanced Full Synthetic formulation
- Formulated for use where fuel economy oils are specified
- Provides fuel saving capability due to advanced additive technology and GF-5 requirements.
- Suitable for European, American and Japanese engines calling for a low viscosity 0w20 engine oil
- Provides reduced oxidation and viscosity breakdown
- Rapid flow technology at start up, minimising engine wear
- Actively locks away harmful performance-robbing deposits
- Helps to remove sludge
- Helps to protect against wear and neutralize corrosive combustion acids
- Helps to maintain protection throughout the oil-drain interval

MEETS THE FOLLOWING SPECIFICATIONS:

API SN/SM

ILSAC GF-5, GF-4



M-Syn 0w20

TYPICAL CHARACTERISTICS

	TEST METHOD	UNITS	RESULTS
Density @ 15°C	ASTM D1298	kg/L	0.846
Kinematic Viscosity			
@ 40°C	ASTM D445	cSt	44
@ 100°C	ASTM D445	cSt	8.3
Viscosity Index	ASTM D2270	-	>165
Pour Point	ASTM D97	°C	-39
Flash Point (COC)	ASTM D92	°C	200
Total Base Number	ASTM D2896	mgKOH/g	7.3
Sulphate Ash	ASTM D874	% mass	<0.8

THE FEATURES MENTIONED ABOVE ARE AVERAGE VALUES OBTAINED WITH SOME VARIABILITY IN PRODUCTION AND DO NOT CONSTITUTE A SPECIFICATION

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained from our website www.monsterlubricants.com.au.

PO BOX 442
RAMSGATE NSW 2217
INFO@MONSTERLUBRICANTS.COM.AU
WWW.MONSTERLUBRICANTS.COM.AU