



M-Syn 5w40

DESCRIPTION

M-Syn SAE 5w40 is a 100% technically advanced fully synthetic engine lubricant that delivers the viscosity required by many European manufacturers. Exceeding industry standards, this oil has been designed to provide excellent fuel efficiency and exceptional engine wear, particularly at cold start ups and is formulated using the latest in API & ACEA additive technology.

Exceeding the needs of today's more demanding modern engines using the latest additives designed to extend the life of your engine and reduce sludge. M-Syn SAE 5w40 is Suitable Petrol, Diesel, LPG cars, light commercial vehicles and 4WDs where API SN/SM/SL/SJ/CF ACEA A3/B3/B4 or earlier specifications are recommended.

FEATURES & BENEFITS

- Designed to increase protection and drain intervals over mineral & semi-synthetic oils
- Provides fuel saving capability due to advance additive technology
- Provides reduced oxidation and viscosity breakdown
- Rapid flow technology at start up, minimising engine wear
- Actively locks away harmful performance-robbing deposits
- Helps to remove sludge
- Helps to protect against wear and neutralize corrosive combustion acids
- Helps to maintain protection throughout the oil-drain interval

MEETS THE FOLLOWING SPECIFICATIONS:

- SAE Viscosity 5w40
- API SN/SM/SL/SJ
- ACEA A3/B3 & A3/B4
- MB 229.3 & 229.5
- BMW LONGLIFE-98 & LONGLIFE-01
- VW 502 00/505 00
- PORSCHE A40



M-Syn 5w40

TYPICAL CHARACTERISTICS

	TEST METHOD	UNITS	RESULTS
Density @ 15°C	ASTM D1298	kg/L	0.88
Kinematic Viscosity			
@ 40°C	ASTM D445	cSt	97
@ 100°C	ASTM D445	cSt	15.2
Viscosity Index	ASTM D2270		>165
Pour Point	ASTM D97	°C	-34
Flash Point (COC)	ASTM D92	°C	210
Total Base Number	ASTM D2896	mgKOH/g	10.1
Sulphated Ash	ASTM D874	% mass	1.15

THE FEATURES MENTIONED ABOVE ARE AVERAGE VALUES OBTAINED WITH SOME VARIABILITY IN PRODUCTION AND DO NOT CONSTITUTE A SPECIFICATION

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained from our website www.monsterlubricants.com.au.

PO BOX 442
RAMSGATE NSW 2217
INFO@MONSTERLUBRICANTS.COM.AU
WWW.MONSTERLUBRICANTS.COM.AU